# Trusted, secure ID issuance







The complete range of ID card printers, all with security built in.

## HoloKote® - inbuilt visual security

### HoloKote - added visual **security** at no extra cost

HoloKote, patented by Magicard, is a secure watermark that is frosted into the clear protective overcoat during the normal print process using standard consumables (ribbons and cards). It can be visually verified when the card is tilted in the light.



### HoloPatch® enhanced visual security

HoloPatch cards have a highly reflective gold 'super diffuser' seal. When the HoloKote watermark is printed onto the seal, it becomes a distance visible security mark enabling security verification from a range of six feet or more.



### Your logo as a customised security watermark

With the Magicard Rio Pro 360, the HoloKote watermark can be customised to an organisation's logo, or some other unique security design. LYNK now enables the secure online delivery of up to ten bespoke HoloKote watermarks to the printer through the driver interface. This makes it possible for customers to start producing secure ID cards in far less time than is required by a custom holographic overlaminate solution, and at a fraction of the cost.



## Our promise to keep you printing

### The best **support** in the industry

Magicard's online and telephone support sets the benchmark for the ID printer industry. A comprehensive online portal with selfhelp, training videos and up-to-date downloadables is backed up by a global network of highly-trained technical support engineers, all available to take your call.



### The best warranty in the industry

The reliability of Magicard's well established print engine is backed by some of the best warranty terms in the industry. Both the Rio Pro 360 and Prima 4 are backed with a 3-year UltraCoverPlus warranty that includes:

- Replacement of a damaged printhead no matter what the cause of failure
- A hot-swap loaner if a printer is shipped to a Certified Magicard Support Hub for repair

The Pronto and Enduro3E printers are backed with 2 and 3 year depot warranties respectively.





88

## ID card printing made easy

ronto











Incredibly easy to use with drop-in dye film and hand-fed card loading, the Pronto includes the HoloKote® visual security system and can print colour, monochrome or rewritable cards.

Its plug-and-play setup and compact footprint are ideal for portability and lower volume card printing.

#### Printer

Print technology 300 dpi dye sublimation/rewritable. Card thickness 0.51mm to 1.02mm (20 mil to 40 mil).

USB rev.1.1/USB 2.0. Printer interface

Drivers/software Windows XP, Vista, 7, 8, 10 (32 and 64bit) Windows server 2003 R2 SP2, 2008, 2012, 2016. Mac OS X 10.9.0 upwards. Linux with CUPS support. Dimensions W 215mm x H 233mm x D 270mm (W 8.4" x H 9.1" x D 10.6")

4.4 kg/9.7 lb. Weight

OSPREY LEISURE

HER PROPERTY.

Operating environment Sheltered office environment 10°C - 30°C (50°F - 85°F).

#### Security

HoloPatch® card stock - ordered separately. Magnetic stripe encoding HiCo and LoCo encoder ISO std. 7811. Smart card encoding Contact chip, MIFARE®, DESFire®, iClass® options.

#### Security watermark

HoloKote (4 standard designs)

-	100	-	100	100	1000		9 9	9 6	0	6	•	0	0	•	0	•				
-0	100	-0	1	100	=0		34	16	6	6	•	0	0	$\oplus$	0	$\oplus$				
-0	100	-	100	100	100		a 9	10	6	6	0	0	0	•	0	$\oplus$				
100	100	100	100	10	20	61	<b>a</b> n G	16	6	6	<b>a</b>	<b>a</b>	<b>a</b>	6	<b>a</b>	@	HARE			MAN

#### **Features**

#### Standard







#### Optional







## The World's most reliable card printer

**Enduro**3E





00









Robust, durable and reliable, the Enduro3E is perfect for schools, colleges and medium sized businesses that print up to 10,000 cards per year. This established ID card printing platform includes Ethernet as standard and a 3 year warranty. When it comes to secure and reliable ID card printing, you can trust the Enduro3E to deliver.

#### Printer

Print technology 300 dpi dye sublimation/rewritable Card thickness 0.51mm to 1.02mm (20 mil to 40 mil). Printer interface USB rev.1.1/USB 2.0, Ethernet.

Drivers/software Windows XP, Vista, 7, 8, 10 (32 and 64bit) Windows server 2003 R2 SP2, 2008, 2012, 2016. Mac OS X 10.9.0 upwards. Linux with CUPS support. Dimensions W 206mm x H 233mm x D 453mm (W 8.1" x H 9.2" x D 17.8").

5.5 kg/12 lb. Weight

Operating environment Sheltered office environment 10°C - 30°C (50°F - 85°F)

#### Security

HoloPatch® card stock - ordered separately. Magnetic stripe encoding HiCo and LoCo encoder ISO std. 7811. Smart card encoding Contact chip, MIFARE®, DESFire®, iClass® options

Security watermark

HoloKote (4 standard designs).

-	-	-	1000	10-10	-0	0	6	0	0	0	6	•	•	•	•	•	0	W				1888
-0	-0	100	100	10-10 10-10 10-10	-						Ğ	0						MAAAF	MAAA	MAAA	10005	1000
11-0	1-0	100	100		100						6	0	•	0	0	•	•	<b>###</b>	###	****	****	-
100	100			100	100		6	6	6	6		•	•	•	•	•	•					

#### **Features**

#### Standard











#### Optional













RITY AAAA

The industry standard

has advanced

Magicard has raised the bar. The Rio Pro 360 is everything users love about the original Rio Pro but with faster print speed, increased capacity and improved print quality. The 360 also has the all new 'LYNK' onboard intelligence - for identity with an IQ.

The 360 is Magicard's fastest printer to date. From the moment you hit print, the 360 instantly gets to work. Full colour cards with a secure, customisable HoloKote® watermark take just 18 seconds click-to-card.

















This is a printer with intelligence. The 360 is the first desktop ID card printer with an embedded Linux-based CPU. This enables seamless communication and the secure processing of ID data - just imagine it's got a brain onboard.

LYNK recognises High Speed USB 2.0 and 10/100 Ethernet and can easily be integrated with most third-party applications locally or in the cloud. WiFi connectivity 802.11 b/g/n will soon be available.

#### Printer

Security

Magnetic stripe encoding

Smart card encoding

Security watermark -----

-----

To the the the the

Gold seal

Print technology 300 dpi dye sublimation/rewritable. Card thickness 0.51mm to 1.02mm (20 mil to 40 mil).

Printer interface High Speed USB 2.0, USB 3.0 compatible - Type B, 10/100 Ethernet.

2x internal USB 2.0 (one host) - Type A. Windows XP, Vista, 7, 8, 10 (32 and 64bit) Windows server 2003 R2 SP2, Drivers/software

2008, 2012, 2016. Mac OS X 10.9.0 upwards. Linux with CUPS support.

W 220mm x H 250mm x D 470mm (W 8.6" x H 9.8" x D 18.5").

4.7 kg/10.4 lb.

Operating environment Sheltered office environment 10°C - 30°C (50°F - 85°F)

#### **Features**

#### Standard

Optional

























HoloPatch® card stock - ordered separately

HiCo and LoCo encoder ISO std. 7811.

HoloKote (10 standard designs).



Contact chip, MIFARE®, DESFire®, iClass® options. Other encoders available.





























Custom HoloKote® - Grid or full card pattern. Up to ten custom designs can be added through the driver interface using the online HoloKote tool.





## Photo quality printing and lamination in a desktop package



FIPS-201 certified for the personalisation of US Government credentials, the Prima 4 provides the most reliable, robust solution for instant issuance in a compact package.

Using retransfer printing technology, the Prima 4 produces cards with a photo quality comparable to offset lithographic printing.

Optional UV printing, holographic lamination and multiple encoding options add an additional layer of security and durability.











#### Printer

300 dpi retransfer with 600 dpi option Print technology Card thickness 0.25mm to 1.00mm (10mil to 40mil).

Printer interface USB 2.0, Ethernet.

Drivers/software Windows 2000 Professional (SP4), XP (SP2, SP3), Vista (SP1), Windows Server 2003 R2 SP2, Server 2008, 2012, Windows 7, 8, 10 (32 and 64 bit). 343mm W x 320mm H x 330mm L (13.5" W x 12.6" H x 13" L).

Weight 15.5kg (34.1lbs).

Operating environment Sheltered office environment 10°C - 30°C (50°F - 85°F).

#### Security and durability

Printer security Kensington lock, electronic lock for hopper and door, security ribbon erase. Magnetic stripe encoding HiCo encoder ISO std. 7811 Smart card encoding

Contact chip, MIFARE®, DESFire®, iClass® options. Others available.

#### U٧



Available with YMCK-UV film only

#### Standard laminates





Patch with cutout



Holographic full card

Customised laminates

Holographic patch

#### **Features**

Standard









#### Optional







Blank patch











Specialist printer



Specialist printer

### Secure your localised credential issuance



The Rio Pro 360 Secure features an opaque, lockable input hopper to secure blank cards. A secondary lock prevents the printer from being opened by unauthorised personnel and secures the opaque output stacker cover.

## Xtend your card printing capability



An adaptation of the Rio Pro 360 print platform, with an extra large hopper and stacker, the Rio Pro 360 Xtended prints oversized cards up to 140mm (5.51") long for ticketing, accreditation and events.

## Printer specification matrix / consumables



Printing	Pronto	Enduro3E	Rio Pro 360	Prima 4
Print technology	Dye sublimation/rewritable	Dye sublimation/rewritable	Dye sublimation/rewritable	Retransfer
Feed system	Manual	Manual/automatic	Manual/automatic	Automatic
Card capacity: input/output	_	100/30	100/70 or 200/70	100/100
- Single-sided	3649-0001	3633-3001	3652-3001	Prima 401
- Double-sided	_	3633-3021	3652-3021	Prima 402
Upgrade (single to double-sided)	_	3633-0052	3633-3052	_
Laminator	_	_	_	Prima 451 (Uno) / Prima 452 (Duo
Encoding / variants				
Magnetic stripe ISO 7811 - tracks 1, 2 & 3				
- Single-sided	3649-0002	3633-3002	3652-3002	_
- Double-sided	_	3633-3022	3652-3022	Prima 403
Smart card (contact chip, MIFARE®, DESFire®, iClass®)				
- Single-sided	3649-0003	3633-3005	3652-3003	Prima 406
- Double-sided	_	3633-3025	3652-3023	Prima 415
Other smart card configurations available	-	_	9	8
Connectivity and drivers				
USB connection	•	•	High Speed 2.0	•
Ethernet connection	_	<b>9</b>	⊕	<b>9</b>
Windows XP, Vista, 7, 8, 10 (32/64bit) Windows server 2003 R2 SP2, 2008, 2012 and 2016	⊖	⊌	⊌	(Windows 2016 not supported)
Mac OS X 10.9.0 upwards. Linux with CUPS support	⊜	⊖	⊖	-
Warranty				
Limited	2 years	3 years	_	_
3 years UltraCoverPlus* - (hot-swap loaner & printhead cov	ver) –	_	⊖	⊖
/isual security				
HoloKote® watermark - standard design	x4	x4	x10	_
HoloKote watermark - custom design	_	_	Up to 10 custom designs	_
UV film	_	_	_	<u> </u>
HoloPatch® cards	<u> </u>	<u> </u>	9	_
Standard/custom overlaminate - patch and continuous	_	-	-	⊖
Print speed				
Colour	35 seconds per card	>100 cards per hour	>200 cards per hour	>100 cards per hour
Monochrome	7 seconds per card	>500 cards per hour	>750 cards per hour	
Card thickness				
mm	0.51 to 1.02	0.51 to 1.02	0.51 to 1.02	0.25 to 1.02
mil	20 to 40	20 to 40	20 to 40	10 to 40
Dimensions				
Width x height x depth : mm	215 x 233 x 270	206 x 233 x 453	220 x 250 x 470	343 x 320 x 330
Width x height x depth : inch	8.4 x 9.1 x 10.6	8.1 x 9.2 x 17.8	8.6 x 9.8 x 18.5	13.5 x 12.6 x 13
Weight kg/lb	4.4/9.7	5.5/12	4.7/10.4	15.5/34
Maintenance				
	CK1	3633-0053	3633-0053	E9887

ronto, Enduro3E and Rio Pro 360 films	Capacity	Product code
Colour film with overcoat panel (YMCKO)	100	MA100YMCKO
Colour film with overcoat panel (YMCKO)	300	MA300YMCKO
Colour film with black panel on reverse (YMCKOK)	250	MA250YMCKOK
Black resin film with overcoat panel (KO)	600	MA600KO
Monochrome resin film - Black	1000	MA1000K-Black
Monochrome resin film - White	1000	MA1000K-White
Monochrome resin film - Blue	1000	MA1000K-Blue
Monochrome resin film - Red	1000	MA1000K-Red
Monochrome resin film - Green	1000	MA1000K-Green
Monochrome resin film - Silver	1000	MA1000K-Silver
Monochrome resin film - Gold	1000	MA1000K-Gold



Important: Printer warranty is subject to the observance of specific conditions of use and maintenance, including printer registration and the use of certified 'Original Magicard' dye films.

Prima 4 films	Capacity	Details	Product code
Film sets	1000 images per set	YMCK film/retransfer film sets (x5)	Prima 431
	1000 images	YMCK film/retransfer film set (x1)	Prima 431/S
Dye film Retransfer film	750 images 750 images 1000 images	YMCKK film, black panel on reverse YMCK-UV film with UV panel Retransfer film	Prima 433 Prima 434 Prima 436
Patch laminate film	600 patches	Clear patch laminate 0.6mil	Prima 462
	600 patches	Clear patch laminate 0.6mil chip cutout	Prima 463
	600 patches	Clear patch laminate 1.0mil	Prima 464
	600 patches	Clear patch laminate 1.0mil chip cutout	Prima 465
Overlay film	1000 overlays	OVD 'snowflake' design film	Prima 461
	1000 overlays	Clear OVD film	Prima 466
Custom laminates	1000/600	Custom overlay film/0.6mil patch laminate	Contact us

#### Global offices













Absolute Access ID, LLC 800 S. Gay Street Suite 700 Knoxville, TN 37929

Phone: 865-771-9697

Web: absoluteaccessid.com

Magicard, HoloKote, Custom HoloKote, HoloPatch, Rio Pro 360, Enduro3E, Pronto and Prima4 are trademarks or registered trademarks of Magicard Ltd. All other trademarks, or and names, or product names belong to their respec

The information contained in this document reflects the current state of design and we reserve the right to change the specification without notice or obligation.

\*UK, EU, North America and selected other territories. Elsewhere a minimum of one year limited warranty.